



RG 213 Mil-C-17

Coaxial Cable 50 Ohm bas. on Mil-C-17

Image representative of cable family. Actual cable may vary.

CPR certified

Based on Mil-C-17

RF communication systems

STANDARDS AND CERTIFICATES

Standards	EN50117-1:2019, EN 50575
CPR Class	Fca
DOP	1002674
ROHS II	complies

CONSTRUCTION

Inner conductor	7x Φ 0,75mm copper strand
Insulation	Φ 7,25mm solid PE
Outer conductor	copper braid
Outer Sheath	Φ 10,30mm PVC black

ELECTRICAL CHARACTERISTICS

Impedance	50 +/-2 Ohm
Nom.Capacitance	100 pF/m
Velocity ratio (V/C)	0,66
Sheath spark test	5 KV
DC resistance	
Inner/Outer conductor	6,0/4,5 Ohm/km
Nom.Attenuation (dB/100m)	
100 MHz	6,80
400 MHz	14,00
800 MHz	22,00
2150 MHz	41,50

MECHANICAL CHARACTERISTICS

Minimum bending radius	
Single/Repeated bending	50/100 mm
Maximum tensile force	400 N
Standard packaging	5x100m, 1x500m

! Cable is not intended for direct connection to the mains electricity supply.

Pentalofos, T. 2310 787202
P.O.Box 10229
54012 Thessaloniki - Greece
welcome@accordia.gr
www.accordia.gr