



## RG 58 Mil-C-17 HF

Coaxial Cable 50 Ohm bas. on Mil-C-17

Image representative of cable family. Actual cable may vary.

**CPR certified**

**Halogen Free**

**Based on Mil-C-17**

**RF communication systems**

### STANDARDS AND CERTIFICATES

Standards	EN50117-1:2019, EN 50575
CPR Class	Fca
DOP	1002596
ROHS II	complies

### CONSTRUCTION

Inner conductor	19x $\Phi$ 0,18mm tinned copper strand
Insulation	$\Phi$ 2,95mm solid PE
Outer conductor	tinned copper braid
Outer Sheath	$\Phi$ 4,95mm HFFR black UV resistant

### ELECTRICAL CHARACTERISTICS

Impedance	50 +/-2 Ohm
Nom.Capacitance	100 pF/m
Velocity ratio (V/C)	0,66
Sheath spark test	4 KV
DC resistance	
Inner/Outer conductor	38,0/15,0 Ohm/km
Nom.Attenuation (dB/100m)	
100 MHz	15,00
400 MHz	34,00
800 MHz	51,50
1000 MHz	60,00

### MECHANICAL CHARACTERISTICS

Minimum bending radius	
Single/Repeated bending	25/50 mm
Maximum tensile force	90 N
Standard packaging	5x100m, 1x500m

**!** Cable is not intended for direct connection to the mains electricity supply.

Pentalofos, T. 2310 787202  
P.O.Box 10229  
54012 Thessaloniki - Greece  
welcome@accordia.gr  
www.accordia.gr