



## Accordia Loudspeaker RB series

Flexible Loudspeaker Cable

Image representative of cable family. Actual cable may vary.

### Flat Audio Cable

CPR certified

Pure copper (min. 99,99% Cu)

### STANDARDS AND CERTIFICATES

Standards	EN 60228 EN 50575
CPR Class	Fca
DOP	1002699
ROHS II	complies

### CONSTRUCTION

Cores	
Cores No	2
Material	Flexible pure copper class 5
Outer Sheath	PVC red-black

### ELECTRICAL CHARACTERISTICS

DC Resistance	0,50mm <sup>2</sup> <39,00 Ohm/km 0,75mm <sup>2</sup> <26,00 Ohm/km 1,00mm <sup>2</sup> <19,50 Ohm/km 1,50mm <sup>2</sup> <13,30 Ohm/km 2,50mm <sup>2</sup> <7,98 Ohm/km
---------------	--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

### OTHER CHARACTERISTICS

Operation temperature	-20 C up to +70 C
Standard packaging	50mm <sup>2</sup> : 10x100m, 2x500m 0,75mm <sup>2</sup> : 10x100m, 2x500m 1,00mm <sup>2</sup> : 7x100m, 2x350m 1,50mm <sup>2</sup> : 5x100m, 2x250m 2,50mm <sup>2</sup> : 3x100m, 2x150m

### OUTER DIMENSIONS

No Cores X Cross-section	Appr. Outer Sheath (mm)
2x 0,50 mm <sup>2</sup>	2,0 x 4,1
2x 0,75 mm <sup>2</sup>	2,2 x 4,4
2x 1,00 mm <sup>2</sup>	2,5 x 5,0
2x 1,50 mm <sup>2</sup>	3,0 x 6,0
2x 2,50 mm <sup>2</sup>	4,0 x 8,0

**!** Cable is not intended for direct connection to the mains electricity supply.

Pentalofos, T. 2310 787202  
P.O.Box 10229  
54012 Thessaloniki - Greece  
welcome@accordia.gr  
www.accordia.gr