



## Accordia Defencer SC8 TS B2ca HFFR

Security Alarm Cable Shielded, Halogen Free

Image representative of cable family. Actual cable may vary.

**CPR class B2ca s1,d1,a1**

**FlameSmart® τεχνολογία**

**Halogen Free**

**Tinned pure copper  
conductors**

**DC Resistance <100 Ohm/km**

**Shielded with aluminum tape**

**Based on BS 4737-3.30,  
Type 1**

### STANDARDS AND CERTIFICATES

Standards	Based on BS 4737-3.30, Type 1 EN 50575
CPR Class	B2ca s1,d1,a1
DOP	1002718
ROHS II	complies

### CONSTRUCTION

Cores No	8
Core's construction	Tinned pure copper
Core's Insulation	HFFR
Laying up	Cores stranded
Core Identification	Different colors without repetition
Screen	Aluminum tape + drain wire
Ripcord	Yes
Outer Sheath (approx.)	Φ 5,30mm HFFR white

### ELECTRICAL CHARACTERISTICS

DC Resistance	<100,0 Ohm/km (<95,0 Ohm/km typical)
Max Operating Voltage	50 V

### OTHER CHARACTERISTICS

Operation temperature	-10 C up to +70 C
Standard packaging	5x100m, 2x250m

**!** Cable is not intended for direct connection to the mains electricity supply.

Pentalofos, T. 2310 787202  
P.O.Box 10229  
54012 Thessaloniki - Greece  
welcome@accordia.gr  
www.accordia.gr